

Specifications (Portable Station KX-TCA385/285/185)

	KX-TCA385	KX-TCA285	KX-TCA185
Model No.	KX-TCA385	KX-TCA285	KX-TCA185
LCD Size	1.8 inch, Backlight (Colour)	1.8 inch, Backlight (Colour)	1.8 inch, Backlight (Colour)
LCD Contrast	6 levels	6 levels	6 levels
LED	Ringer/Charge	Ringer/Charge	Ringer/Charge
Handset Phonebook (PBX)	Up to 500 Numbers	Up to 500 Numbers	Up to 500 Numbers
Call Log -Incoming/Outgoing Calls (PBX)	10/5	10/5	10/5
Flexible CO Keys	12	12	12
Soft Keys	3	3	3
Redial	Yes	Yes	Yes
Message Waiting Indication	Yes	Yes	Yes
3-Party Conferencing	Yes	Yes	Yes
DECT Paging	Yes	Yes	Yes
Bluetooth®	Yes (Built-in)	Yes (Built-in)	No
Phonebook Transfer via Bluetooth®	Yes (vCard V2.1)	Yes (vCard V2.1)	N/A
Noise Reduction	Yes	Yes	Yes
Splash and Dust Resistant	IP65	N/A	N/A
Speaker Phone (Full Duplex)	Yes	Yes	Yes
Headset Port	N/A	Yes (2.5 mm mini pin jack)	Yes (2.5 mm mini pin jack)
Handset, Speaker, Headset Volume	6 levels	6 levels	6 levels
Ringtones	27	27	27
Ringer Volume	6 levels + Off	6 levels + Off	6 levels + Off
Vibrate Ring	Yes	Yes	Yes
Battery Talk/Standby Time*	Up to 13 hours/Up to 200 hours	Up to 13 hours/Up to 200 hours	Up to 11 hours/Up to 200 hours
Battery Charge Time	3 hours	3 hours	7 hours
Battery Type	Li-ion battery pack x 1	Li-ion battery pack x 1	Ni-MH AAA battery x 2
Belt Clip	Yes (Clip type is included)	Yes (Swivel type is included)	Yes (Swivel type is included)
Operating Environment	When in use	0 °C - 40 °C (32 °F - 104 °F)	0 °C - 40 °C (32 °F - 104 °F)
	When charging	5 °C - 40 °C (41 °F - 104 °F)	5 °C - 40 °C (41 °F - 104 °F)
Dimensions (Width x Depth x Height; handset on cradle, stand attached)	(Headset)	55 mm x 23 mm x 151.5 mm	48.5 mm x 17.9 mm x 127.5 mm
	(Headset on Charger)	71.5 mm x 80.5 mm x 165 mm	63 mm x 78 mm x 140 mm
Weight (with handset, handset cord and stand)	(Headset)	150 g (Belt clip is included)	88 g
	(Headset on Charger)	200 g	135 g

\*Operating time may be shorter than listed above depending on usage conditions and ambient temperature.

Maximum Portable Stations and Cell Stations\*

Type	Model No.	KX-NS1000		KX-NCP1000	KX-NCP500	KX-TDE600	KX-TDE200	KX-TDE100	KX-TDA600	KX-TDA1000	KX-TDA100/200	KX-TDA30
		Stand-alone System	One-look Networking									
Portable Stations	KX-TCA Series	512	512	64	64	512	128	128	512	128	128	28
Cell Station	KX-NCP0158 (8ch, LAN I/F)	64	128	16	16	16	16	16	N/A	N/A	N/A	N/A
	KX-TDA0158 (8ch, DPT I/F)	32	64	5	3	64	16	16	64	13	16	4
	KX-TDA0156 (4ch, CS I/F)	64	128	N/A	N/A	128	32	32	128	26	32	N/A
	KX-TDA0155 (2ch, DPT I/F)	64	128	11	7	128	32	32	128	26	32	8

\* Contact your dealer for further information.

IP Cell Station



**KX-NCP0158**  
LAN I/F  
8ch speech paths

Cell Station



**KX-TDA0158**  
DPT I/F  
8ch speech paths

**KX-TDA0155**  
DPT I/F  
2ch speech paths  
**KX-TDA0156**  
CS I/F  
4ch speech paths

Repeater



**KX-A405**  
A repeater can be used to extend the range.

Trademarks and registered trademarks

- The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Panasonic Corporation is under licence. Other trademarks and trade names are those of their respective owners.

Important

- Safety Precaution: carefully read the operating instructions and installation manual before using these products.

- Some models are available in limited countries.
- The images shown of product displays and lamps are composite images.
- Weights and dimensions are approximate.
- Design and specifications subject to change without notice.
- These products may be subject to export control regulations.

DISTRIBUTED BY :

**Panasonic**

**Panasonic**

Multi-cell  
DECT System

**KX-TCA385**  
**KX-TCA285**  
**KX-TCA185**



KX-TCA385



KX-TCA285



KX-TCA185